



## Cutting Oil

### DESCRIPTION

**FOXX Gold HT (Hydro treated)** is cutting and grinding oil. It is formulated with a hydro-treated base oil and special lubricants. It is clear in appearance and recommended for use on automatic lathe and general machining of ferrous and nonferrous metals.

### FEATURES & BENEFITS

- Very low odor with a transparent pale yellow appearance
- Additives and base oils are selected to be mild on operators skin.
- Oxidation resistant/chemical stability – Assists in extending the service life of metalworking oil.
- Excellent surface finish – Special lubricants are added to improve cutting performance and surface finish while extending tool life.
- Reduce fumes – The use of a low viscosity and high flash point premium base oil makes FOXX Gold HT (Hydro treated) low fuming in service.

### TYPICAL PHYSICAL AND CHEMICAL PROPERTIES

Specific Gravity (15/4°C) . . . . .	0.8780
Flash Point( °C) . . . . .	150
Viscosity(40°C,cSt). . . . .	20.0
Chlorine(%) . . . . .	-
Sulfur(%) . . . . .	-
Fat(%) . . . . .	5.0
Copper Corrosion Test(100°C/1hr) . . . . .	1a
Color(ASTM). . . . .	0.5

### PACKAGING

20 litre pails, 200 litre drums, and bulk containers

*For additional information on FOXX Gold HT (Hydro treated) refer to its MSDS or contact CIMCOOL Technical Services e-mail: [info@cimcoolapac.com](mailto:info@cimcoolapac.com) · Reprints/updates: [www.cimcool.com](http://www.cimcool.com) This product is sold by Cimcool Korea Asia Pacific, a Milacron Marketing Company, Cincinnati, Ohio 45209. Minor formulation changes or normal variations in the manufacture of this product may cause slight variances in the data presented on this sheet.*